

## Ceiling installation



Screws are fitted in predrilled holes with washers if ceiling is in plastic.

The holes should face the roof beam.

Start fitting screws from the middle towards the edges and corners.

If hinges are provided, they are used on the edges of the ceiling to support loose areas.

Clip the hinge in the panel and use short 13mm screws to fit the hinge in the van's body. Make sure not to damage any cables or to drill through the van chassis!

H-profile between the parts could be included in the kit for some models.


Quality product of



**KOSKISEN**

www.koskisen.com

### Ceiling installation

- » Make sure that you have the correct parts and accessories for your van model.
- » Remove the original panels if necessary.
- » Use compatible tools to assembly all the accessories and use only original Kore accessories for your ceilings.
- » Install in accordance with the ceiling drawing.
- » Make sure that parts correctly fit your van before final fixing.
- » Please note: on some models (e.g. VW Caddy 5) the front of the ceiling is fitted between the chassis (roof) and the partition wall.
  - » Make sure not to damage any electrical cables etc. whilst fixing the parts.
- 
  - » Check the run of the cables before starting installation.
- » Remember to use appropriate length screws to avoid damage by drilling through the van body. Check this before drilling!
- » Install the parts so that there are even gaps between the panels and that the ceiling parts are evenly centred from the edges.
- » Some ceiling sets have an aluminium profile or a plastic H-profile between the ceiling parts.
  - » The H-profile needs to be fitted between the parts; fix front part, add H-profile, fix 2nd part an so on.
  - » An aluminium profile is fixed afterwards at the joint.
- » The ceiling panel has predrilled holes where you need to use the provided screws or plugs to fix the ceiling. These holes will face the van's roof beams. If the ceiling is in plastic material, use the plastic washer with the screw.
- » When using screws, start fixing the ceiling panels from the middle and continue towards the edges and corners.
- » If plastic hinges are included, those can be used with 13mm screws to fix any loose or hanging points on the edges of the ceiling panel. Some positions for the hinges are already marked in the parts with small cut-outs. Please add hinges over any loose areas if needed but make sure not to damage the van or cables.
- » If you need more support, please contact your distributor or the Kore Service Center.